


## mobiSTEEL-3000 I-double-walled

steel-tank accessories-230 V-65 I-F



**Item number:** 26 789 960  
**EAN:** 4103810422997  
**Discount group:** D

### Technical data

**Tank**  
 Tank volume (l): 3000  
 UN approval: un 31A/Z/...\*/PL/SPAW-MAL/6588/3660  
 UN certificate: UN/16/1591/13  
 Material of container: Steel sheet  
 Material of end caps: Steel sheet  
 Wall thickness (mm): 3  
 Color of container: grey, RAL 7042  
 Colour of cover: grey, RAL 7042

**Pump**  
 Brand: FMT Swiss AG  
 Connecting cable, length (m): 2  
 Pump design: vane pump, selfpriming

**Hydraulic data**  
 Duty cycle (min): continuous operation – a real endurance runner  
 Delivery rate under free discharge (l/min): 65  
 Discharge pressure (bar): 1,8  
 Pumping media: fuel oil and diesel

**Motor data**  
 Voltage (V): 230  
 Power consumption (A): 3  
 Safety class: IP66

**Digital in-line meter**  
 Temperature range (°C): -10 / +60  
 Display: 5 digits display

**Dimensions LxWxH (mm):** 2460 x 1630 x 1350  
**Empty weight (kg):** 1160

### Specification

- Double wall steel tank (45 204)
- Tank truck connector (80 514)
- Level indicator (85 142 100)
- Overfill sensor (83 723)
- Ventilation valve (45 140)
- 1 Piece suction set G 1" for pump with vane, suction hose, non return valve and drainer (89 011 010)
- 1 Piece suction set G 3/4" for power generator with suction hose, non return valve and drainer (89 011 001)
- 1 piece connection for return line G 1/2" from power generator (89 010 002)
- Universal securing trap for shackle
- Lockable cap
- In-line meter, digital (23 190)

- Discharge hose, 6 m, DN 19, G 1" male, G 1" female (23 155 958)
- Diesel-exchange filter, 30 µm (23 209)
- Vane pump, with integral bypass (23 430)
- Automatic nozzle valve with swivel joint, ZVAD (23 176)

**Special notes**

- European ADR Certificate for transportation of dangerous liquids on public roads
- Fillable up to 90 % and transportable according to ADR
- Transportable by forklift and crane lugs
- 2 tanks could be stacked
- Integrated filter holds back condensation water
- Level indicator, mechanical
- Manhole enables access to the inner tank
- 3 outlets for delivery/gazole return with closed cover

**Packaging**

Dimensions LxWxH (mm):	2460 x 1630 x 1350
Weight (kg):	1160
Packing unit:	1,0