





Army-fuel can-20 l

PE-with flexible spout

Item number: EAN: Discount group: 21 127 4103810211270 A

Technical data Capacity (I): UN approval:

Material jerrycan:HEColour of can:datMaterial jerrycan locking cap andadapter:adapter:polMaterial discharge spout and fixationstrap:LDColour locking cap:recColour fixation strap and adapter:Stength of discharge spout:whLength of discharge spout outside (mm):24Diameter discharge spout outside (mm):20Height (mm):480Base LxB (mm):350Weight (kg):1,4

20

un 3H1/Y/150/..../CZ/PRES-IMET 1228 As of 01.06.2015, all fuel cans (UN) must be marked by the end user in accordance with the GHS / CLP Regulation. For identification use our labels, Item no. (80 967). HDPE (high density polyethylene) dark grey, RAL 7021

polypropylene

LDPE (polyethylene of low density) red, RAL 3001 steel-grey, RAL 7011 white, transparent 245 20 480 350 x 175 1,45

Specification

- With flexible spout
- Spout is stored inside jerrycan
- Spout with integrated ventilation
- Cover cap is secured against loss with flexible band
- With EAN bar code

Special notes

- No contamination of the discharge spout when storing the jerrycan in a vehicle
- No rusty splits in the fuel
- Less water condensate in the jerrycan
- 1,45 kg total weight instead of 4,85 kg of the metal version
- Integral discharge spout to be stored in the jerry can complete with patented jerrycan locking cap
- Dimensions compatible with military jerrycans
- Lower conductibility of temperature in comparison to metal version
- Suitable for liquid fuels
- Robust and resistant against impact
- UN-approval

Packaging

Packing unit:

1,0