



**Barrel pump**

SRL 355-955-18 l/min

**Item number:** 13 012  
**EAN:** 4103810130120  
**Discount group:** A

**Technical data**

Delivery rate (l/stroke): 0,3  
 Delivery rate at 60 strokes/min (l/min): 18  
 Pumping media: oils up to SAE 90  
 Usage: container for 60 / 200 / 220 l  
 Discharge: discharge spout, fastened by cap nut  
 Length of suction tube (mm): 355  
 Immersion depth (two-part) (mm): 355 - 625  
 Immersion depth (three-part) (mm): 685 - 955  
 Barrel screw coupling: G 2" male

**Materials of parts in contact with liquid**

Pump head: impact-resistant zinc die casting  
 Pump body: aluminium  
 Suction pipe: HDPE (high density polyethylene)  
 discharge rigid nozzle: PP  
 Seals: PVC, NBR, FKM

Weight (kg): 1,59

**Specification**

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Ergonomic handle, non-slip, excellent power transfer and handling
- Packed in single carton box
- With EAN bar code

**Special notes**

- Suitable for use in conjunction with engine oil from SAE 5 W to SAE 50, gear oil from SAE 75 W to SAE 90, fuel oil, diesel, machine oil, cutting oil, petroleum, undiluted anti-freeze
- The ease of dismantling permits simple cleaning
- A check valve can be easily installed without any tools in the suction tube
- The check valve prevents the fluid from flowing back into the container

**Packaging**

Dimensions LxWxH (mm): 800 x 90 x 90  
 Weight including package (kg): 1,77  
 Packing unit: 1,0