

| SRL 355-955-24 I/min-ABGS 6 m-ZVMU | | |
|---|----------------------------------|--|
| ltem number: EAN: Discount group: | 13 040 950 4048358701428 A | |
| Discount group. | ~ | |
| Technical data | | |
| Delivery rate (l/stroke): | 0,4 | |
| Delivery rate at 60 strokes/min (l/min): | 24 | |
| Pumping media: | AdBlue®, urea | |
| | water | |
| | screen cleaners | |
| | antifreeze | |
| Usage: | container 60/200/220 I | |
| Length, three-part suction pipe (mm): | 355 - 955 | |
| Barrel screw coupling: | G 2" male | |
| | | |
| Materials of parts in contact with liquid | | |
| Pump body: | ABS / PA 6 | |
| Seals: | FKM + HNBR | |
| | 0.04 | |
| Weight (kg): | 3,61 | |
| | | |

Specification

- Pump housing with piston, hand lever and discharge spout
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085)
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- AdBlue® discharge hose, DN 19, 6 m, with bend 90° G 1" female and swivel joint for ZVMU (25 671)
- Packed in single carton box

Special notes

- Constant delivery rate for many years
- Completely dismountable easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Flexible positionining
- Optional barrel adapters: (13 085 001) barrel adapter S 56x4; (13 085 002) barrel adapter S 69,5x5,5; (13 085 003) barrel adapter M 64x4 male; (13 085 006) barrel adapter S 64x5
- 3 year warranty (excluding wearable parts)
- Non-return valve, (13 097), optional for telescopic suction tube (13 094)

Packaging

| Dimensions LxWxH (mm): | 675 x 285 x 430 |
|--------------------------------|-----------------|
| Weight including package (kg): | 4,92 |
| Packing unit: | 1,0 |



PRESSO

