

Barrel pump for AdBlue®-G 2"

SRL 355-955-24 l/min-ABGS 6 m-ZVMU



Item number: 13 040 950
EAN: 4048358701428
Discount group: A

Technical data

Delivery rate (l/stroke): 0,4
Delivery rate at 60 strokes/min (l/min): 24
Pumping media: AdBlue®, urea, water, screen cleaners, antifreeze
Usage: container 60/200/220 l
Length, three-part suction pipe (mm): 355 - 955
Barrel screw coupling: G 2" male

Materials of parts in contact with liquid

Pump body: ABS / PA 6
Seals: FKM + HNBR

Weight (kg): 3,61

Specification

- Pump housing with piston, hand lever and discharge spout
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085)
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- AdBlue® discharge hose, DN 19, 6 m, with bend 90° G 1" female and swivel joint for ZVMU (25 671)
- Packed in single carton box

Special notes

- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Flexible positioning
- Optional barrel adapters: (13 085 001) barrel adapter S 56x4; (13 085 002) barrel adapter S 69,5x5,5; (13 085 003) barrel adapter M 64x4 male; (13 085 006) barrel adapter S 64x5
- 3 year warranty (excluding wearable parts)
- Non-return valve, (13 097), optional for telescopic suction tube (13 094)

Packaging

Dimensions LxWxH (mm): 675 x 285 x 430
Weight including package (kg): 4,92
Packing unit: 1,0



