



Rotary pump blue

with accessories-SRL 355-955 mm-18 l/min

Item number: 13 056
EAN: 4103810130564
Discount group: A

Technical data

Delivery rate (l/rotation): 0,3
 Delivery rate at 60 rotations/min; pumping medium diesel (l/min): 18
 Pumping media: self-lubricating and non-aggressive media: fuel oil
 diesel
 petroleum
 cooling fluid (undiluted)
 do not use aqueous solutions
 radiator antifreeze only undiluted
 machine maintenance: hydraulic oil
 cutting fluid
 gear oil, oils up to SAE 90
 Length of discharge hose (mm): 2000
 Container: 60/200/220 l
 Application: for filling measuring vessels, storage cans, canisters and machines
 Discharge: Discharge hose with steel spout
 Length, three-part suction pipe (mm): 355 - 955
 Barrel screw coupling: G 2" male
 Material pump housing: impact-resistant zinc die casting ZL 410
 Colour crank: silver
 Colour gear cover and gear housing: blue
 Color of housing: blue
 Weight (kg): 3,475

Specification

- Telescopic suction tube (13 094), with infinitely variable length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (13 098)
- Discharge hose, 2 m, with steel discharge spout (13 044 020)
- Hose holder (00 845)

Special notes

- Smooth hand-rotating operation
- The pump is continuously positionable in 360°
- Suction tube flexible in length from 355 to 955 mm
- Assembly, commissioning and container change without tools
- CNC machined, thus optimum pump efficiency
- All connections sealed trough gaskets and O-rings
- Completely dismantable - easy to clean
- Spare parts available for 10 years
- Available in 4 colour variantes

- Warranty 5 years when using the supplied suction basket (excluding wear parts)
- 0,3 liter per revolution



Packaging

Dimensions LxWxH (mm):	400 x 395 x 220
Weight including package (kg):	4,32
Packing unit:	1,0

13056
Kurbelpumpe Migu
mit ZOH-SRL 355-955 mm-18l/min

