



Rotary pump blue

with accessories-SRL 355-955 mm-18 l/min

Item number: 13 056
EAN: 4103810130564
Discount group: A

Technical data

Delivery rate (l/rotation): 0,3
Delivery rate at 60 rotations/min; pumping medium diesel (l/min): 18
Pumping media: self-lubricating and non-aggressive media: fuel oil, diesel, petroleum, coolant fluid (undiluted); machine maintenance: hydraulic oil, cutting fluid, gear oil, oils up to SAE 90
Usage: container for 60 / 200 / 220 l
Application: for filling measuring vessels, storage cans, canisters and machines
Length of discharge hose (mm): 2000
Discharge: Discharge hose with steel spout
Length, three-part suction pipe (mm): 355 - 955
Barrel screw coupling: G 2" male
Material pump housing: impact-resistant zinc die casting ZL 410
Colour crank: silver
Colour gear cover and gear housing: blue
Color of housing: blue
Weight (kg): 3,475

Specification

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (81 112)
- Discharge hose, 2 m, with anti-kink spring and steel discharge spout (13 075 020)
- Hose holder (00 845)

Special notes

- Smooth hand-rotating operation
- The pump is continuously positionable in 360°
- Suction tube flexible in length from 355 to 955 mm
- Assembly, commissioning and container change without tools
- CNC machined, thus optimum pump efficiency
- All connections sealed trough gaskets and O-rings
- Completely dismountable - easy to clean
- Spare parts available for 10 years
- Available in 4 colour variantes
- Warranty 5 years when using the supplied suction basket (excluding wear parts)
- 0,3 liter per revolution

Packaging

Dimensions LxWxH (mm): 400 x 395 x 220
Weight including package (kg): 4,32
Packing unit: 1,0

