



Rotary pump blue

with accessories-SRL 355-955 mm-18 l/min

Item number:

13 056

EAN:

4103810130564

Discount group:

A

Technical data

Delivery rate (l/rotation):

0,3

Delivery rate at 60 rotations/min;

pumping medium diesel (l/min):

18

Pumping media:

self-lubricating and non-aggressive media:
fuel oil

Length of discharge hose (mm):

2000

diesel

petroleum

cooling fluid (undiluted)

do not use aqueous solutions

radiator antifreeze only undiluted

machine maintenance:

hydraulic oil

cutting fluid

gear oil, oils up to SAE 90

60/200/220 l

Container:

for filling measuring vessels, storage cans,
canisters and machines

Discharge:

Discharge hose with steel spout

Length, three-part suction pipe (mm):

355 - 955

Barrel screw coupling:

G 2" male

Material pump housing:

impact-resistant zinc die casting ZL 410

Colour crank:

silver

Colour gear cover and gear housing:

blue

Color of housing:

blue

Weight (kg):

3,475



Specification

- Telescopic suction tube (13 094), with infinitely variable length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (13 098)
- Discharge hose, 2 m, with steel discharge spout (13 044 020)
- Hose holder (00 845)

Special notes

- Smooth hand-rotating operation
- The pump is continuously positionable in 360°
- Suction tube flexible in length from 355 to 955 mm
- Assembly, commissioning and container change without tools
- CNC machined, thus optimum pump efficiency
- All connections sealed through gaskets and O-rings
- Completely dismountable - easy to clean
- Spare parts available for 10 years
- Available in 4 colour variants



- Warranty 5 years when using the supplied suction basket (excluding wear parts)
- 0,3 liter per revolution



Packaging

Dimensions LxWxH (mm): 400 x 395 x 220
Weight including package (kg): 4,32
Packing unit: 1,0

13056
Kurbelpumpe blau
mit ZBH-SRL 395-955 mm-180/min

