



## Rotary pump blue

with accessories-SRL 355-955 mm-18 l/min

**Item number:** 13 056  
**EAN:** 4103810130564  
**Discount group:** A

### Technical data

**Delivery rate (l/rotation):** 0,3  
**Delivery rate at 60 rotations/min;**  
**pumping medium diesel (l/min):** 18  
**Pumping media:** self-lubricating and non-aggressive media:  
 fuel oil  
 diesel  
 petroleum  
 coolant fluid (undiluted)  
 do not use aqueous solutions  
 radiator antifreeze only undiluted

**Length of discharge hose (mm):** 2000  
 machine maintenance:  
 hydraulic oil  
 cutting fluid  
 gear oil, oils up to SAE 90  
 container for 60 / 200 / 220 l  
 Usage:  
 Application: for filling measuring vessels, storage cans,  
 canisters and machines

**Discharge:** Discharge hose with steel spout  
**Length, three-part suction pipe (mm):** 355 - 955  
**Barrel screw coupling:** G 2" male  
**Material pump housing:** impact-resistant zinc die casting ZL 410  
**Colour crank:** silver  
**Colour gear cover and gear housing:** blue  
**Color of housing:** blue  
**Weight (kg):** 3,475

### Specification

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (81 112)
- Discharge hose, 2 m, with steel discharge spout (13 044 020)
- Hose holder (00 845)

### Special notes

- Smooth hand-rotating operation
- The pump is continuously positionable in 360°
- Suction tube flexible in length from 355 to 955 mm
- Assembly, commissioning and container change without tools
- CNC machined, thus optimum pump efficiency
- All connections sealed trough gaskets and O-rings
- Completely dismountable - easy to clean
- Spare parts available for 10 years
- Available in 4 colour variantes

- Warranty 5 years when using the supplied suction basket (excluding wear parts)
- 0,3 liter per revolution

**Packaging**

Dimensions LxWxH (mm): 400 x 395 x 220

Weight including package (kg): 4,32

Packing unit: 1,0

