



FMS set for AdBlue®

Item number: 25 497
EAN: 4048358254979

Technical data

Number of users (iButton): 1000
 Number of vehicles: 1000
 Number of vehicles per user: 50
 Type of user ID: PIN and/or iButton
 Type of display and size: illuminated 5"-LCD display
 Compatible operating systems: Linux, MAC, Windows
 Voltage (V): 230
 Frequency (Hz): 50
 Power consumption (A): 0,25
 Safety class: IP54
 Connecting cable with Euro two-pin plug, length (m): 2
 Maximum settable dispensing quantity (l): 0-999
 The tank level for re-filling can be adjusted when the tank is empty (L): 0-999
 Note
 The level for re-filling will be arithmetically calculated
 Level indication (L) optional in connection to art.no: 0-10.000
 Number of filling stations: 2
 Dimensions LxWxH (mm): 240 x 156 x 56

Specification

- SD card, reader for SD card with USB connector
- Software and operating instructions on CD-ROM
- 7 iButtons in black for users (5 pcs), red for service (1 pc) and green for supervisor (1 pc)
- Fluid Management System (FMS) in aluminium housing (23 499)
- Control nozzle storage bracket (23 166) with cable, 3 m, and connecting plug (83 012) for connection with FMS
- Stainless steel pulse meter (IPG) (23 823) with cable, 3 m and connecting plug (83 012)

Special notes

- An integral heating in the FMS provides an operation and a clearness of the display even at low temperatures (tested until -25 °C).
- Two tanks can be operated with the FMS
- User identification by PIN and/or by iButton
- User friendly PC application for configuration and installation of storage tanks, tank volumes, users and vehicles
- The PC application checks for available updates every 10 days
- All data can be installed on a PC and can be transferred with a SD card to the FMS
- The data of any refilling process can be readout on a PC and can be exported for special analysis. A USB adapter for the SD card is part of the product.

- The SD card supplied offers space for the storage of several thousands of refilling processes.

Packaging

Dimensions LxWxH (mm): 370 x 225 x 205

Packing unit: 1,0