



DEF FMS set

Item number: 25 497 006
EAN: 4048358708816

Technical data

Number of users (iButton): 1000
 Number of vehicles: 1000
 Number of vehicles per user: 50
 Type of user ID: PIN and/or iButton
 Type of display and size: illuminated 5"-LCD display
 Compatible operating systems: Linux, MAC, Windows
 Voltage (V): 120
 Frequency (Hz): 60
 Power consumption (A): 0.25
 Safety class: IP54
 Connecting cable, length (ft): 6.56
 Maximum settable dispensing quantity (gal.): 0-263.91
 The tank level for re-filling can be adjusted when the tank is empty (gal.): 0-263.91
Note
 The level for re-filling will be arithmetically calculated
 Level indication (gal.) optional in connection to art.no. (23 068): 0-2641.7
 Number of filling stations: 2
 Dimensions LxWxH (inch): 9.45 x 6.14 x 2.20

Specification

- SD card, reader for SD card with USB connector
- Software and operating instructions on CD-ROM
- 7 iButtons in black for users (5 pcs), red for service (1 pc) and green for supervisor (1 pc)
- Fluid Management System (FMS) in aluminium housing (23 499 006)
- Control nozzle storage bracket (23 166) with cable, 3 m, and connecting plug (83 012) for connection with FMS
- Stainless steel pulse meter (IPG) (23 823 006) with cable, 3 m and connecting plug (83 012)

Special notes

- An integral heating in the FMS provides an operation and a clearness of the display even at low temperatures (tested until -13 °F)
- Two tanks can be operated with the FMS
- User identification by PIN and/or by iButton
- User friendly PC application for configuration and installation of storage tanks, tank volumes, users and vehicles
- The PC application checks for available updates every 10 days
- All data can be installed on a PC and can be transferred with a SD card to the FMS
- The data of any refilling process can be readout on a PC and can be exported for special analysis. A USB adapter for the SD card is part of the product.
- The SD card supplied offers space for the storage of several thousands of refilling processes.

Packaging

Dimensions LxWxH (inch):

14.57 x 8.86 x 8.07

Packing unit:

1,0