



AdBlue® trolley-200 I-8 I/min

Elaflex-ISO-22241-5-230 V-50 Hz

 Item number:
 25 337 836

 EAN:
 4048358708694

Discount group:

Technical data

Pump

Connecting cable, length (m): 2

Hydraulic data

Pump design: diaphragm pump, selfpriming

Delivery rate under free discharge

(l/min): 14 Discharge pressure up to (bar): 1,7

Pumping media: AdBlue®, water

Motor data

Voltage (V): 230
Frequency (Hz): 50/60
Power consumption (A): 1,5

Duty cycle (min): continuous operation – a real endurance runner

Safety class: IP66

Trolley load (kg): 200

Dimensions LxWxH (mm): 1200 x 840 x 270

Weight (kg): 39

Specification

AdBlue® supply system, mobile

- For 200/220 I container
- Diaphragm pump, selfpriming (25 284)
- Suction tube for IBC (83 396)
- AdBlue® suction hose, DN 19, 1 m, with SEC adapter and bend 90° with spout (25 657)
- Trolley (17 077)
- AdBlue® discharge hose, DN 13, 4 m, with bend 90° G 1" female and swivel joint for automatic nozzle valve ZVAUD 10 I (25 683)
- Automatic nozzle Elaflex for AdBlue® with filler neck according to ISO 22241-5 (23 171 836)

Special notes

• Dispensing valve exchange container with water reservoir

Packaging

Packaging: Carton

Dimensions LxWxH (mm): 950 x 840 x 270

Weight including package (kg): 48,39 Packing unit: 1,0











