

Fuel can-5 l

PE-with flexible spout

Item number:	21 141
EAN:	4103810211416
Discount group:	A

Technical data

Capacity (l):	5
UN approval:	un 3H1 / Y /100/ CZ / PRES - IMET 18100 As of 01.06.2015, all fuel cans (UN) must be marked by the end user in accordance with the GHS / CLP Regulation. For identification use our labels, Item no. (80 967).
Material jerrycan:	HDPE (high density polyethylene)
Colour of can:	dark grey, RAL 7021
Material jerrycan locking cap and adapter:	polypropylene
Material discharge spout and fixation strap:	LDPE (polyethylene of low density)
Colour locking cap:	red, RAL 3001
Colour fixation strap and adapter:	steel-grey, RAL 7011
Colour discharge spout:	white, transparent
Length of discharge tube (mm):	175
Diameter discharge spout outside (mm):	20
Height (mm):	251
Base LxB (mm):	329 x 152
Weight (kg):	0,44

Specification

- Flexible discharge spout with integral ventilation
- Spout is stored inside jerrycan
- Cover cap is secured against loss with flexible band
- With EAN bar code

Special notes

- Suitable for liquid fuels
- With two-side view line and scale to monitor the fill level
- Reduced effort application through the recessed grip
- No rusty splits in the fuel
- Less water condensate in the jerrycan
- Integral discharge spout to be stored in the jerry can complete with patented jerrycan locking cap
- No contamination of the discharge spout when storing the jerrycan in a vehicle
- Lower conductibility of temperature in comparison to metal version
- Robust and resistant against impact
- UN-approval

Packaging

Packing unit:	1,0