







Barrel pump-G 2" -M 64x4

SRL 355-955-24 l/min

Item number:	13 044
EAN:	4103810130441
Discount group:	A

Technical data

Delivery rate (l/stroke):	0,4
Delivery rate at 60 strokes/min (l/min):	24
Pumping media:	oils up to SAE 50, diesel, petroleum, kerosene, glycerin and antifreeze undiluted
Usage:	container 60/200/220 l
Length, three-part suction pipe (mm):	355 - 955
Barrel screw coupling:	G 2" male and M 64x4 male

Materials of parts in contact with liquid

Pump body:	ABS + PA6
Seals:	FKM
Metal pieces:	steel, galvanized stainless steel steel, powder coated
Weight (kg):	1,24

Specification

- Pump housing with piston, hand lever and discharge spout
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085) and barrel screw coupling M 64x4 (13 085 003)
- Discharge hose, 1500 mm, with steel discharge spout (13 044 010)
- Hose holder (00 845)
- Discharge spout (13 098)
- Valuable sales package

Special notes

- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Can be freely positioned in 30° increments
- Optional barrel adapters: barrel adapter S 56x4 (13 085 001); barrel adapter S 69,5x5,5 (13 085 002); barrel adapter M 64x4 male (13 085 003); barrel adapter S 64x5 (13 085 006)
- 3 year warranty (excluding wearable parts)
- Suction strainer, (13 097 003), optional for telescopic suction tube (13 094)

Packaging

Dimensions LxWxH (mm):	395 x 243 x 125
Weight (kg):	2,3
Packing unit:	1,0









13044
Fasspumpe-G 2"-M 64x4
SNL 355-955-24 l/min

