



Barrel pump-G 2" -M 64x4

SRL 355-955-24 l/min

Item number: 13 044
EAN: 4103810130441
Discount group: A

Technical data

Delivery rate (l/stroke): 0,4
Delivery rate at 60 strokes/min (l/min): 24
Pumping media: oils up to SAE 50, diesel, petroleum, kerosene, glycerin and antifreeze undiluted
Usage: container 60/200/220 l
Length, three-part suction pipe (mm): 355 - 955
Barrel screw coupling: G 2" male and M 64x4 male

Materials of parts in contact with liquid

Pump body: ABS + PA6
Seals: FKM
Metal pieces: steel, galvanized
 stainless steel
 steel, powder coated

Weight (kg): 1,24

Specification

- Pump housing with piston, hand lever and discharge spout
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085) and barrel screw coupling M 64x4 (13 085 003)
- Discharge hose, 1500 mm, with steel discharge spout (13 044 010)
- Hose holder (00 845)
- Discharge spout (13 098)
- Valuable sales package

Special notes

- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Can be freely positioned in 30° increments
- Optional barrel adapters: barrel adapter S 56x4 (13 085 001); barrel adapter S 69,5x5,5 (13 085 002); barrel adapter M 64x4 male (13 085 003); barrel adapter S 64x5 (13 085 006)
- 3 year warranty (excluding wearable parts)
- Suction strainer, (13 097 003), optional for telescopic suction tube (13 094)

Packaging

Dimensions LxWxH (mm): 395 x 243 x 125
Weight (kg): 2,3
Packing unit: 1,0





13044
Fichtensäge G 2" M 6x4
SR 355-955-24 1/min

